



*BLIND RIVET TOOL ATSRL4000SV
FOR BLIND RIVETS*

*TECHNICAL DATA SHEET
ATSRL4000SV
Approv. Dir.
UNI EN ISO 9001:2015 REG.3023/A
CERTIFIED COMPANY*

BLIND RIVET TOOL ATSRL4000SV FOR BLIND RIVETS



| Weight | Air Pressure | Max. Stroke | Max. Traction Power |
|---------|--------------|-------------|---------------------|
| 1,12 Kg | 5 – 7 bar | 18 mm | 4850 N |

| Rivet Type | Rivet Material | 2,4mm | 3,2mm | 4,0mm |
|-----------------------|----------------------|-------|-------|-------|
| Standard Rivets | Aluminium-Aluminium | ● | ● | ● |
| | Aluminium-Steel/Inox | ● | ● | ● |
| | Steel-Steel | ● | ● | ● |
| | Inox-Inox | ● | ● | ● |
| Sealed Blind Rivets | Aluminium-Aluminium | ● | ● | ● |
| | Steel-Steel | ● | ● | ● |
| | Aluminium-Steel | ● | ● | ● |
| | Inox-Inox | ● | ● | ● |
| Bulb Type Rivets | Aluminium-Aluminium | ● | ● | ● |
| Multigrip Type Rivets | Steel-Steel | ● | ● | ● |
| Graff Type Rivets | Aluminium-Steel | ● | ● | ● |

The values expressed are indicative

It is forbidden to reproduce this document and disclose it to third parties with reference to a confidentiality agreement as it is the property of A.T.S. S.R.L.